



PRODUCT DESCRIPTION

The strong, clean lines of the Candela™ present a look that's chic and contemporary. Featuring two precise frosted bands of luminescent LED light, it offers a fresh, on-trend addition to entryways, bedrooms and walk-in closets..

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using-replaceable LEDs with greater than or equal to 90 CRI (color rendering index).

THE CORDOVA MIRRORS ADVANTAGE

- ☑ High-quality products at a value price
- ☑ Carefully chosen, globally sourced materials
- ☑ Natural-looking LED lighting for a superior reflection
- ☑ Best-in-class customer service team
- ☑ In-stock products ready for immediate shipment

FEATURES AND BENEFITS

- Copper-free, corrosion-resistant PrimeMirror™ glass
- Forward-facing task lighting
- Energy efficient
- Easy installation
- 3-year limited warranty
- Covered by one or more patents

AVAILABLE OPTIONS

- Cord connect
- Custom mirror sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 556 lumens per foot
- L₇₀ 36,000-hour LED lifespan
- Maximum 96 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror

Note: Minimum order quantity may apply. Contact sales@cordovamirrors.com for information.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options

MODELS

Base Model*	Dimensions	Power Requirements
CAN2-26.00x60.00-LSO-OS-30K	26"W x 60"H x 1.83"D (660mm x 1524mm x 46.5mm)	120/240 VAC, 51W

* Base model numbers shown only. To specify additional options, contact Cordova Mirrors at sales@cordovamirrors.com.

** Due to mirror chassis hanging system, mirror can only be installed in width and height orientation specified; it can't be rotated 90° to swap width and height dimensions.

DIMENSIONAL DRAWING (Not to scale.)

