



### PRODUCT DESCRIPTION

An attractive and functional alternative to wall sconces, Nuria™ pairs natural-looking forward-facing illumination with soft wall glow, forming a visionary blend of task and ambiance lighting.

### SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting as well as left and right side wall-glow ambient lighting. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index).

### THE CORDOVA MIRRORS ADVANTAGE

- ☑ High-quality products at a value price
- ☑ Carefully chosen, globally sourced materials
- ☑ Natural-looking LED lighting for a superior reflection
- ☑ Best-in-class customer service team
- ☑ In-stock products ready for immediate shipment

### FEATURES AND BENEFITS

- Copper-free, corrosion-resistant PrimeMirror™ glass
- Forward-facing task lighting
- Left and right side wall-glow ambient lighting
- Energy efficient
- Easy installation
- ADA compliant
- Title 24 compliance available
- 3-year limited warranty
- Covered by one or more patents

### AVAILABLE OPTIONS

- Cord connect
- Custom mirror sizes
- Touch dimming
- Forward-phase dimming
- 0-10V dimming

### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 636 lumens per foot
- L<sub>70</sub> 50,000-hour LED lifespan
- Maximum 118 lumens per watt efficacy

### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror

Note: Minimum order quantity may apply. Contact [sales@cordovamirrors.com](mailto:sales@cordovamirrors.com) for information.

**INSTALLATION SPECIFICATIONS**

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options
- Mirror can only be hung in the WxH orientation as show and is not field interchangeable

**MODELS**

Base Model*	Dimensions**	Power Requirements
NUR2.1-24.00x36.00-LHO-OS-30K	24"W x 36"H x 1.83"D (610mm x 914mm x 46.5mm)	120/240 VAC, 55W
NUR2.1-36.00x36.00-LHO-OS-30K	36"W x 36"H x 1.83"D (914mm x 914mm x 46.5mm)	120/240 VAC, 55W
NUR2.1-48.00x36.00-LHO-OS-30K	48"W x 36"H x 1.83"D (1219mm x 914mm x 46.5mm)	120/240 VAC, 55W
NUR2.1-60.00x36.00-LHO-OS-30K	60"W x 36"H x 1.83"D (1524mm x 914mm x 46.5mm)	120/240 VAC, 55W

\* Base model numbers shown only. To specify additional options, contact Cordova Mirrors at sales@cordovamirrors.com.

**DIMENSIONAL DRAWING** (Not to scale.)

