



PRODUCT DESCRIPTION

This limited-edition lighted mirror is an elegant upgrade to the immensely popular Celestino™. It features a luxurious 4mm raised mirror surface adjacent to the frosted light that highlights a distinctive edge.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with a 4mm raised mirror surface with a flat-ground edge. Mirror must provide forward-facing task lighting as well as wall-glow ambient lighting around the mirror. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index).

THE CORDOVA MIRRORS ADVANTAGE

- ☑ High-quality products at a value price
- ☑ Carefully chosen, globally sourced materials
- ☑ Natural-looking LED lighting for a superior reflection
- ☑ Best-in-class customer service team
- ☑ In-stock products ready for immediate shipments

FEATURES AND BENEFITS

- Raised mirror surface for added dimension and drama
- Lead-free, copper-free, corrosion-resistant PrimeMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting on all four sides with diffuser for a finished side view
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- 3-year limited warranty
- Covered by one or more patents
- Designed in America and sourced globally

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 720 lumens per foot
- Maximum 96 lumens per watt efficacy
- Calculated L₇₀ 50,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

Note: Minimum order quantity may apply.
Contact sales@cordovamirrors.com for information.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODEL

Base Model	Dimensions	Power Requirements
CEL-FM-36.00X36.00-L7SHD-30K	36"W x 36"H x 2.07"D (914mm x 914mm x 53mm)	120/240 VAC, 85W

DIMENSIONAL DRAWING (Not to scale.)

