



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant PrimeMirror™ glass
- One-touch dimmable inward-facing task lighting for brilliant facial illumination
- One-touch dimmable wall-glow ambient lighting with diffuser for a finished side view
- Greater illuminance with half the power consumption of traditional LED mirrors
- Sleek and modern profile
- Suitable for damp bathroom environments
- Energy efficient
- Easy installation
- Title 24 compliance available
- 3-year limited warranty
- Covered by one or more patents
- Designed in America and sourced globally

AVAILABLE OPTIONS

- Clock^{1, 2}
- Defogger¹
- 0-10V dimming¹
- 220V available^{1, 3}
- Cord connect¹
- Matte black finish standard; other finishes available¹
- Custom sizes¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 324 lumens per foot
- Maximum 96 lumens per watt efficacy
- Calculated L₇₀ 36,000-hour LED lifespan
- Built-in EMX diffusers

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror

¹ Minimum order quantity required

² See technology specification sheets for more details.

³ May not be compatible with all upgrades and options

PRODUCT DESCRIPTION

With brilliant inward-facing directional task lighting and a sublimely sleek look, the Romana™ lighted mirror combines the best of form and function to serve flawlessly in virtually any room.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with integrated one-touch dimming and one-touch wall glow. LEDs will be mounted in a 45-degree channel in the frame of the mirror, with inward-facing directional lighting on the front face of the mirror and ambient wall glow behind the mirror. LEDs shall have an L₇₀ calculated life of 36,000 hours, with a greater than or equal to 90 CRI (color rendering index), and will be covered by an integrated diffuser. Product shall incorporate a mounted driver enclosure that is attached to the back of the mirror. Product will have a 3-year limited warranty.

THE CORDOVA MIRRORS ADVANTAGE

- ☑ High-quality products at a value price
- ☑ Carefully chosen, globally sourced materials
- ☑ Natural-looking LED lighting for a superior reflection
- ☑ Best-in-class customer service team
- ☑ In-stock products ready for immediate shipments

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip
- Junction box is required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming wall switch for on/off, and capacitive touch button on fixture for dimming
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Power Requirements
ROM3-24.00x36.00-15A-TD2-WG3-OS-30K	24"W x 36"H x 2.01"D (610mm x 914mm x 51mm)	120 VAC, 86W
ROM3-36.00x36.00-15A-TD2-WG3-OS-30K	36"W x 36"H x 2.01"D (914mm x 914mm x 51mm)	120 VAC, 105W
ROM3-48.00x36.00-15A-TD2-WG3-OS-30K	48"W x 36"H x 2.01"D (1,219mm x 914mm x 51mm)	120 VAC, 122W
ROM3-60.00x36.00-15A-TD2-WG3-OS-30K	60"W x 36"H x 2.01"D (1,524mm x 914mm x 51mm)	120 VAC, 139W

*Base model number shown only. To specify additional options, contact Cordova Mirrors at sales@cordovamirrors.com.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

