


Eliseo™ Series 1 Lighted Mirror

Product Specifications: Multifamily Standard Output LEDs

CORDOVA®
BY ELECTRIC MIRROR



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant PrimeMirror™ glass
- Forward-facing task lighting
- Suitable for damp bathroom environments
- Energy efficient
- Easy installation
- Title 24 compliance available
- 3-year limited warranty
- Designed in America and sourced globally

AVAILABLE OPTIONS

- Touch dimming^{1,2}
- Nightlight^{1,2}
- Clock^{1,2}
- Bluetooth^{1,2}
- Defogger¹
- CCT: 2,700K¹
- 0-10V dimming¹
- Forward-phase dimming¹
- 277V available^{1,3}
- Cord connect¹
- Custom sizes¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 516 raw lumens per foot
- Maximum 96 lumens per watt efficacy
- Calculated L₇₀ 50,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ Minimum order quantity required.

² See technology specification sheets for more details.

³ May not be compatible with all upgrades and options.

PRODUCT DESCRIPTION

Encapsulating a clear vision of renewal and balance, the Eliseo™ unites a romantic shape with a stunning circle of brilliant light and boldly illuminates your space with timeless elegance.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will have a 3-year warranty.

THE CORDOVA MIRRORS ADVANTAGE

- ☑ High-quality products at a value price
- ☑ Carefully chosen, globally sourced materials
- ☑ Natural-looking LED lighting for a superior reflection
- ☑ Best-in-class customer service team
- ☑ In-stock products ready for immediate shipments

Eliseo™ Series 1 Lighted Mirror

Product Specifications: Multifamily Standard Output LEDs

CORDOVA®
BY ELECTRIC MIRROR

INSTALLATION SPECIFICATIONS

- 120V hardwire electrical connection; provide 36" whip; junction box not required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Lumens	Power Requirements
ELO1-21.00X30.00-EC-LSO-OS-30K	21"W x 30"H x 1.75"D (610mm x 762mm x 45mm)	2,666 lumens per fixture	120 VAC, 30W
ELO1-30.00-EC-LSO-OS-30K	30" Diameter x 1.75"D (762mm x 45mm)	3,268 lumens per fixture	120 VAC, 36W
ELO1-36.00-EC-LSO-OS-30K	36" Diameter x 1.75"D (914mm x 45mm)	4,042 lumens per fixture	120 VAC, 45W

*Base model number shown only. To specify additional options, contact Cordova Mirrors at sales@cordovamirrors.com.

DIMENSIONAL DRAWING (Not to scale)

