



PRODUCT DESCRIPTION

The Renato™ features two frosted bands of luminescent LED light accentuated by a bold, contemporary frame, offering a striking focal point for any room.

SPECIFICATION STATEMENT

Solution shall consist of a framed, lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will have a 3-year warranty.

THE CORDOVA MIRRORS ADVANTAGE

- ☑ High-quality products at a value price
- ☑ Carefully chosen, globally sourced materials
- ☑ Natural-looking LED lighting for a superior reflection
- ☑ Best-in-class customer service team
- ☑ In-stock products ready for immediate shipments

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant PrimeMirror™ glass
- Forward-facing task lighting
- Suitable for damp bathroom environments
- Energy efficient
- Easy installation
- ADA compliant
- Title 24 compliance available
- 3-year limited warranty
- Covered by one or more patents
- Designed in America and sourced globally

AVAILABLE OPTIONS

- Touch dimming^{1, 2}
- Nightlight^{1, 2}
- Clock^{1, 2}
- Defogger¹
- 0-10V dimming¹
- Forward-phase dimming¹
- 277V available^{1, 3}
- Cord connect¹
- Urban Profile frame ebony finish standard; other finishes available¹
- Custom frames¹
- Custom sizes¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 516 lumens per foot
- Maximum 96 lumens per watt efficacy
- Calculated L₇₀ 36,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ Minimum order quantity required.

² See technology specification sheets for more details.

³ May not be compatible with all upgrades and options.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Power Requirements
REN2.1-29.00x41.00-LSO-OS-30K	29"W x 41"H x 2.13"D (737mm x 1041mm x 54mm)	120/240 VAC, 29W
REN2.1-41.00x41.00-LSO-OS-30K	41"W x 41"H x 2.13"D (1041mm x 1041mm x 54mm)	120/240 VAC, 29W

*Base model number shown only. To specify additional options, contact Cordova Mirrors at sales@cordovamirrors.com.

DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

